DAILY DRILLING REPORT

RPT DATE: 11/17/2020
RPT NUM.: 29
RIG: Frontier Rig 16

WELL/JOB INFORMATION

WELL NAME: FORGE 16A [78]-32	JOB: Drilling 65° Tangent	RIG SUPERV: Duane Winkler, Leroy Swearingen, Virgi
FIELD:	LEASE:	RIG PHONE: 281-854-6858
AFE #:	API #:	EMAIL:
CONTRACTOR: Frontier Drilling	ELEVATION: 5415.1	RKB:
SPUD DATE: 10/30/2020	DFS: 18	DOL: 28
MD/TVD: 5473	24 HR FTG: 83	HRS DRLG: 7.5

PRESENT OPERATIONS: LOGGING WITH SCHLUMBERGER. RUN #1 ISOLATION SCANNER LOG, RUN #2 TEMPERATURE LOG

ACTIVITY PLANNED: RIG DOWN SCHLUMBERGER. PICK UP CORE TOOLS AND TRIP IN HOLE TO CORE AT 5,473'

BOP

LAST BOP TEST: 12/14/20 | LAST BOP DRILL: 11/6/20 | NEXT BOP TEST: 11/14/20

CASING

CASING TYPE	OD	WEIGHT	GRADE	MD	TVD
Conductor	20.00	54	A53B	130	130
Surface	13.38	68	L-80	1,629	1,629
Intermediate	9.63	40	HCL-80	5,113	5,112

MUD

TIME	MW	FV	WL	PH	CAKE	GELS (10s/10m/30m)			PV	YP	CL	K	Pf	Mf	Ca	OIL	LGS	HTHP
18:00	8.8	48.0	7.8	11.5	1	8	15	25	20	25	1,400		0.85	2.40			2.30	

DRILL BITS

NO.	SIZE	MANUFACTURER	TYPE	SER NO.	JETS	TFA	RE-RUN	IN	OUT	FEET	HRS	WOB	RPM	ROP
10	8.75	Ulterra	PDC	54132	6x14	0.900	N	5,345	5,473	128	7.5	52	89	17.1
9	8.75	SMITH	PDC	JV2705	4x12, 4x11	0.910	N	5,113	5,345	232	15.5	50	89	15.0

BIT NO. 10 | INNER: 1 | OUTER: 1 | DULL: RR | LOC: A | SEAL: | GAUGE: I | OTHER: | RP: CP

PUMPS

PUMP	MAKE	MODEL	LINER	STK	SPM	PSI	GPM	GPS	EFF %	ECD	AV DP	AV DC	BIT HHP	PUMP HHP
2	BOMCO	1600	6.000	12.000	95	2800	400		95	9.26	138.6	445	52.1	
3	BOMCO	1600	6.000	12.000	95	2800	400		95	9.26	138.6	445	52.1	

BHA

#	COMPONENT	OD	ID	LENGTH	#	COMPONENT	OD	ID	LENGTH
1	Drill Bit-8 3/4" PDC	8.75		0.95	7	Monel Collar-6 3/4" NMDC	6.75		30.35
2	Steerable Assembly-VERTICAL SCOUT	7.13		19.6	8	Drill Collar-6 1/2" DRILL COLLARS	6.5		644.15
3	Motor-SCOUT 7/8 3.0 FIXED	6.5		28.48	9	Drill Pipe-5" HWDP	5	3	276.35
4	Shock Sub-6 1/2" NOV SHOCK SUB	6.75	2.25	10.81					
5	Monel Collar-6 3/4" NM STABILIZER	6.75		6.87					
6	Sub-6 1/2" SCOUT UBHO	6.5	2.75	3.11					

DESCRIPTION: 8 3/4" Directional BHA #10

LENGTH: 1,020.67 | BHA WT. AIR: 58,698 | BHA WT. MUD: 50,800 | HRS. ON JARS:

ROT. WT.: 190,000 | P.U. WT.: 235,000 | S.O. WT.: 200,000 | TORQUE: 3,200

SURVEY DATA

MD	INCLINATION	AZIMUTH	TVD	N/S COORDINATES	E/W	V. SECTION	DLS
5,092	1.56	108.18	5,091	-7.8	3.4	5.3	0.8
5,199	1.63	88.50	5,198	-8.3	6.3	8.3	0.5
5,294	1.67	51.93	5,293	-7.4	8.8	10.4	1.1
5,389	1.32	36.29	5,388	-5.6	10.5	11.6	0.6

CONSUMABLES

CONSUMABLE	DAILY RECEIVED (gal)	DAILY USED (gal)	DAILY ON HAND (gal)
Fuel		1,907	11,716
Potable Water			1,000

TIME BREAKDOWN

FROM	TO	HRS	PHASE	CODE	NPT	OPERATIONS
06:00	13:30	7.5	Production Drilling	Drilling		PJSM, pre job safety meeting Drill ahead from 5.390' to 5,473' with BHA #10 , (83') @ 11 FPH 50K WOB, 40 rotary, 325 psi differential, 575 gpm. SSP 2300 Last survey at 5,389', 1.32° Inc., 36.29° AZI Mw 8.8, viscosity 40
13:30	16:00	2.5	Production Drilling	Trips		Circulate, pump dry pill 1ppg over mud weight Trip out of hole to 1610' shut down
16:00	19:30	3.5	Production Drilling	Cut off Drill Line		Re-spool drilling line on drum. Cut and slip drill line
19:30	22:00	2.5	Production Drilling	Trips		Trip out of hole from 1,610' to top of directional tools. Lay down Scout directional tools. Bit was in gauge and good shape.
22:00	06:00	8.0	Production Drilling	Wire Line Logs		PJSM with Schlumberger and Frontier Drilling. Rig up wireline tools. Log intermediate casing with Schlumberger. Run #1 Isolation Scanner Log, (IBC , CBL) Run #2 Temperature Log.