

Company: University Of Utah

Well: FORGE 78B-32

Field: None

County: Beaver State: Utah

Borehole Profile Log

County:	Beaver						
Field:	None						
Location:	Lat: 38.500171, Long: -112.88221						
Well:	FORGE 78B-32						
Company:	University Of Utah						
Logging Date	Location:		Lat: 38.500171, Long: -112.88221	Elev.:	K.B. 5565.50 ft G.L. 5536.00 ft D.F.		
	Permanent Datum:	Ground Level	Elev.:	5536.00 f			
	Log Measured From:	Kelly Bushing	29.50 ft	above Perm.Datum			
	Drilling Measured From:	Kelly Bushing					
		API Serial No.	Max.Hole Deviation	Longitude:	Latitude:		
	NRC 42-00090-03	0 deg	-112.88221 degrees	38.500171 degrees			

Run Number	1A	
Depth Driller	8540.00 ft	
Schlumberger Depth	8540.00 ft	
Bottom Log Interval	8540.00 ft	
Top Log Interval	2988.00 ft	
Casing Driller Size @ Depth	11.75 in @ 2989.00 ft	
Casing Schlumberger	2988 ft	
Bit Size	8.75 in	
Type Fluid In Hole	Water	
Density	8.3 lbm/gal	
Fluid Loss	PH	
MUD	Source of Sample	Active Tank
RM @ Meas Temp	0.2 ohm.m @ 68 degF	
RMF @ Meas Temp	0.15 ohm.m @ 68 degF	
RMC @ Meas Temp		
Source RMF	RMC	Pressed
RM @ BHT	RMF @ BHT	0.05 @ 320.87 0.03 @ 320.87
Max Recorded Temperatures	321.43 degF	
Circulation Stopped	Time	19-Jul-2021 03:00:00
Logger on Bottom	Time	19-Jul-2021 07:53:00
Unit Number	Location:	9108 F.Morgan
Recorded By		T.Mozena/C.Stiles/I.Nasir
Witnessed By		Virgil Welch


Disclaimer


THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

Contents

- 1. Header
- 2. Disclaimer
- 3. Contents
- 4. Well Sketch
- 5. Borehole Size/Casing/Tubing Record
- 6. Remarks and Equipment Summary
- 7. Depth Summary
- 8. 1A 2"/100' MAIN PASS
  - 8.1 Integration Summary
  - 8.2 Composite Summary
  - 8.3 Log ( 2in Borehole Profile PPC )
  - 8.4 Parameter Listing
- 9. Calibration Report
- 10. Tail

## Well Sketch





Borehole Size/Casing/Tubing Record

Bit						
Bit Size ( in )	22	14.77	10.625	8.75		
Top Driller ( ft )	0	416	2989	8514		
Top Logger ( ft )	0	416	2989	8514		
Bottom Driller ( ft )	416	2989	8514	8540		
Bottom Logger ( ft )	416	2989	8514	8540		
Casing						
Size ( in )	11.75					
Weight ( lbm/ft )	54					
Inner Diameter ( in )	10.88					
Grade	N/A					
Top Driller ( ft )	0					
Top Logger ( ft )	0					
Bottom Driller ( ft )	2989					
Bottom Logger ( ft )	2988					

Remarks and Equipment Summary

1A: Toolstring				1A: Remarks	
<div><div><div>Equip name</div><div>LEH-MT</div><div>LEH-MT</div></div><div><div>Length</div><div>80.89</div></div><div><div>MP name</div><div></div></div><div><div>Offset</div><div></div></div></div> <div><p>The diagram shows a vertical toolstring with several sensors. From top to bottom, the sensors are: Mud Temperature (78.95), CTEM (74.24), ACCZ (0.00), HV (0.00), Gamma Ray (72.37), TelStatus (71.24), and PPC-B Calipers (70.09). The toolstring is color-coded: orange for the top section and blue for the bottom section.</p></div>	Tool was run as per tool sketch			All logging intervals as per client request	
	<div><div><div>EDTC-B:9316</div><div>6</div><div>EDTH-B:8170-19k</div><div>EDTG-A:79527</div><div>EDTC-B:9316</div></div><div><div>PPC-B:8048</div><div>PPC-B:8048</div></div></div> <div><div>Mud Temperature</div><div>78.95</div></div> <div><div>CTEM</div><div>74.24</div></div> <div><div>ACCZ</div><div>0.00</div></div> <div><div>HV</div><div>0.00</div></div> <div><div>Gamma Ray</div><div>72.37</div></div> <div><div>TelStatus</div><div>71.24</div></div> <div><div>PPC-B Calipers</div><div>70.09</div></div>				

MAST-B:843 64.72  
2  
ECH-SF:8453  
MAPC-BA:847  
3  
MAMS-CA:843  
2  
MASS-BA:804  
7  
MAXS-BA:818  
0



MAMS 49.27

**FBST-E:1949**    **23.42**  
ECH-MJA:389  
4  
FBPC-A:818  
AH-287:723  
FBSH-D:882  
FBAC-B:838  
DHRU-F:2822  
FBSS-B:1949



Deviation 9.94  
GPIT-F Inc 9.94  
linometer  
GPIT 0.00

Lengths are in ft  
Maximum Outer Diameter = 5.000 in  
Line: Sensor Location, Value: Gating Offset  
All measurements are relative to TOOL\_ZERO

Depth Summary

	1A		
--	----	--	--

Depth Measuring Device

Type	IDW-JA		
Serial Number	6160		
Calibration Date	30-Sep-2020		
Calibrator Serial Number	57		
Calibration Cable Type	7-46 AXS		
Wheel Correction 1	-9		
Wheel Correction 2	-7		

Tension Device

Type	CMTD-B/A		
Serial Number	946		
Calibration Date	02-Jun-2020		
Calibrator Serial Number	78135A		
Number of Calibration Points	10		
Calibration Root Mean Square Error	8		
Calibration Peak Error	12		

Logging Cable

1A:Depth Control Parameters		Depth Control Remarks
Log Sequence	First Log In the Well	Schlumberger depth control procedures followed
Rig Up Length At Surface		IDW used as primary depth control system
Rig Up Length At Bottom		Z-Chart used as secondary depth control system
Rig Up Length Correction		
Stretch Correction		
Tool Zero Check At Surface		

# 1A

2"/100' MAIN PASS

Integration Summary	
<p><b>Integration Summary</b></p> <p>The integration of the three models (Cognitive-Behavioral, Psychodynamic, and Humanistic) provides a comprehensive framework for understanding human behavior. This summary outlines the key components and their interrelationships.</p>	<p><b>Key Concepts and Interrelationships</b></p> <p>The integration of the three models (Cognitive-Behavioral, Psychodynamic, and Humanistic) provides a comprehensive framework for understanding human behavior. This summary outlines the key components and their interrelationships.</p>

Pass Summary									
Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
1A	Log[2]:Up	Up	2952.88 ft	8529.53 ft	19-Jul-2021 7:53:53 AM	19-Jul-2021 1:26:07 PM	ON	9.38 ft	Yes

Pass Summary	
--------------	--

All depths are referenced to toolstring zero

Log	Company:University Of Utah	Well:FORGE 78B-32
		1A: Log[2]:Up:S015

Well:FORGE 78B-32



Description: Format: Log ( 2in Borehole Profile PPC ) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 19-Jul-2021 23:39:17



Cement		Cement	
Bit Size (BS)		Bit Size (BS)	
23	in	3	in
Future Casing (Outer) Diameter (FCD)		Future Casing (Outer) Diameter (FCD)	
23	in	3	in
Hole Diameter 1 (HD1_PPC1) PPC-B		Integrated Cement Volume	
23	in	ft3	
Integrated Hole Volume		Hole Diameter 2 (HD2_PPC1) PPC-B	
ft3		3	in

Cable Tension (TENS)


21000 lbf 1000



3580.3 2101.9
































































































Cement			Cement		
Bit Size (BS)			Bit Size (BS)		
23	in	3	3	in	23
Future Casing (Outer) Diameter (FCD)			Future Casing (Outer) Diameter (FCD)		
23	in	3	3	in	23
Hole Diameter 1 (HD1_PPC1) PPC-B			Integrated Cement Volume ft3		
23	in	3			
Integrated Hole Volume ft3			Hole Diameter 2 (HD2_PPC1) PPC-B		
			3	in	23

TIME\_1900 - Time Marked every 60.00 (s)

ICV - Integrated Cement Volume every 100.00 (ft3)

ICV - Integrated Cement Volume every 10.00 (ft3)

IHV - Integrated Hole Volume every 100.00 (ft3)

IHV - Integrated Hole Volume every 10.00 (ft3)

Description: Format: Log ( 2in Borehole Profile PPC ) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 19-Jul-2021 23:39:17

## Channel Processing Parameters

### 1A: Parameters

Parameter	Description	Tool	Value	Unit
BHS	Borehole Status (Open or Cased Hole)	Borehole	Open	
BS	Bit Size	WLSESSION	Depth Zoned	in
C1_SHIFT	C1 Caliper Supplementary Offset	FBST-E	0.173	in
C2_SHIFT	C2 Caliper Supplementary Offset	FBST-E	-0.201	in
CBLO	Casing Bottom (Logger)	WLSESSION	2988	ft
CSODDRL	Casing Outer Diameter - Zoned along driller depths	WLSESSION	11.75	in
DPINV_LAGCUT	Lag Cut for Dipole Inversion	MAST-B	No	
DTST_SLO_MFL	Slowness Series of Mouse Clicks for Relabeling DTST_MFL	MAST-B	[0]	us/ft
FCD	Future Casing (Outer) Diameter	WLSESSION	7	in
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS(RT)	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	C1	

### Depth Zone Parameters

Parameter	Value	Start ( ft )	Stop ( ft )
BS	14.77	2970	2989
BS	10.625	2989	8514
BS	8.75	8514	8529.5

All depth are actual.



# Tool Control Parameters

## 1A: Parameters

Parameter	Description	Tool	Value	Unit
AMIP	Adaptive Mode Initial Phase	FBST-E	0	deg
APM	Acquisition Phase Mode	FBST-E	WBM - Adaptive Phase Control	
EMXGMOD	EMEX and Gain Modes	FBST-E	EMEX= Auto and Gain= Auto	
FLM	Logging Mode	FBST-E	Full Image Mode	
GAIN_FBST	Electronic Gain Value in Manual Mode	FBST-E	0 dB	
GARM_A	Electronic Gain Value for Arm A	FBST-E	0 dB	
GARM_B	Electronic Gain Value for Arm B	FBST-E	0 dB	
GARM_C	Electronic Gain Value for Arm C	FBST-E	0 dB	
GARM_D	Electronic Gain Value for Arm D	FBST-E	0 dB	
MAX_LOG_SPEED	Toolstring Maximum Logging Speed	WLSESSION	Time Zoned	ft/h
MPSC	Manual Phase Shift Compensation	FBST-E	0	deg
XVOL	EMEX Voltage	FBST-E	0	V

## Time Zone Parameters

Parameter	Value	Start Time	Stop Time	Start Depth ( ft )	Stop Depth ( ft )
MAX_LOG_SPEED	981	19-Jul-2021 07:53:53	19-Jul-2021 09:18:29	8529.53	7089.48
MAX_LOG_SPEED	1093	19-Jul-2021 09:18:29	19-Jul-2021 09:22:39	7089.48	7020.06
MAX_LOG_SPEED	1020	19-Jul-2021 09:22:39	19-Jul-2021 11:06:44	7020.06	5248.35
MAX_LOG_SPEED	960	19-Jul-2021 11:06:44	19-Jul-2021 11:20:17	5248.35	5025.34
MAX_LOG_SPEED	1010	19-Jul-2021 11:20:17	19-Jul-2021 11:55:38	5025.34	4439.93
MAX_LOG_SPEED	958	19-Jul-2021 11:55:38	19-Jul-2021 12:00:52	4439.93	4353.01
MAX_LOG_SPEED	1026	19-Jul-2021 12:00:52	19-Jul-2021 12:36:12	4353.01	3756.38
MAX_LOG_SPEED	968	19-Jul-2021 12:36:12	19-Jul-2021 12:41:22	3756.38	3666.9
MAX_LOG_SPEED	1022	19-Jul-2021 12:41:22	19-Jul-2021 12:43:26	3666.9	3631.22
MAX_LOG_SPEED	960	19-Jul-2021 12:43:26	19-Jul-2021 12:48:40	3631.22	3539.98
MAX_LOG_SPEED	1009	19-Jul-2021 12:48:40	19-Jul-2021 12:52:51	3539.98	3466.23
MAX_LOG_SPEED	948	19-Jul-2021 12:52:51	19-Jul-2021 12:57:01	3466.23	3393.32
MAX_LOG_SPEED	998	19-Jul-2021 12:57:01	19-Jul-2021 13:19:54	3393.32	2990.73
MAX_LOG_SPEED	1071	19-Jul-2021 13:19:54	19-Jul-2021 13:26:07	2990.73	2952.88

All depth are at tool zero.

## Calibration Report

### PPC-B (Powered Positioning device and Caliper.) Calibration - Run 1A

Primary Equipment :			
PPC-B Element is used for usual logging at wellsite and check/diagnostics.		PPC-B	8048
Auxiliary Equipment :			
PPC-B Element is used for usual logging at wellsite and check/diagnostics.		PPC-B	8048
Calibration Parameter :			
ZERO_REF			
PLUS_REF			
Equipment Properties :			
Caliper Arm Equipment Type for PPC		PPC_CAL_STD	

### PPC Check - Downhole Electronics Test

Before (Measured):		18:55:59 17-Jul-2021					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	

Positive Analog Voltage	V	Before	-----	7	8.67451	9	<div><div></div><div></div><div></div><div></div><div></div></div>
Minus Analog Voltage	V	Before	-----	-9	-8.69063	-7	<div><div></div><div></div><div></div><div></div><div></div></div>
Digital Voltage	V	Before	-----	3.15	3.38352	3.45	<div><div></div><div></div><div></div><div></div><div></div></div>
Digital Voltage for Analog Digital Converter	V	Before	-----	4.5	5.02822	5.5	<div><div></div><div></div><div></div><div></div><div></div></div>
Status Word of Analog Digital Converter Offset		Before	-----	-8	0	8	<div><div></div><div></div><div></div><div></div><div></div></div>
PPC Check - Cartridge Temperature Test							
Before (Measured):		18:55:59 17-Jul-2021					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
Cartridge Temperature	degF	Before	-----	-58	86.1308	482	<div><div></div><div></div><div></div><div></div><div></div></div>
PPC Check - Power Control LVDT Test							
Before (Measured):		18:55:59 17-Jul-2021					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
LVDT5 Caliper Open Position	in	Before	-----	-----	-1.25427	-----	<div><div></div><div></div></div>
LVDT5 Full Power Position	in	Before	-----	-----	1.37488	-----	<div><div></div><div></div></div>
PPC Diagnostics - Arm Close Position Test							
Master:							
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
Caliper-arm 1, radius raw - 0	in	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
Caliper-arm 2, radius raw - 0	in	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
Caliper-arm 3, radius raw - 0	in	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
Caliper-arm 4, radius raw - 0	in	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
Power Control LVDT - 0	in	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
LVDT excitation - 0	V	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
PPC Diagnostics - Downhole Electronics Test							
Master:							
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
Positive Analog Voltage - 0	V	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
Minus Analog Voltage - 0	V	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
Digital Voltage - 0	V	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
Digital Voltage for Analog Digital Converter - 0	V	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
Status Word of Analog Digital Converter Offset - 0		Master	-----	-----	-----	-----	<div><div></div><div></div></div>
PPC Diagnostics - RBS Test							
Master:							
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
Relative Bearing - 0	deg	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
Potentiometer Excitation - 0	V	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
PPC Diagnostics - Cartridge Temperature Test							
Master:							
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
Cartridge Temperature - 0	degF	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
PPC Diagnostics - Power Control LVDT Test							
Master:							
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
LVDT5 Caliper Open Position - 0	in	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
LVDT5 Full Power Position - 0	in	Master	-----	-----	-----	-----	<div><div></div><div></div></div>
PPC LVDT5 Master Calibration - PPC CaliCoefficients							
Master (EEPROM):		19:33:00 17-Jul-2021					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
CCS	in	Master	-1.51	-1.71	-1.43127	-1.31	<div><div></div><div></div><div></div><div></div><div></div></div>
COP	in	Master	-1.31	-1.55	-1.25427	-1.07	<div><div></div><div></div><div></div><div></div><div></div></div>
CPW	in	Master	1.41	1.2	1.37488	1.61	<div><div></div><div></div><div></div><div></div><div></div></div>
PPC Caliper Calibration - PPC CaliCoefficients							
Before (Manual Entry):		19:53:08 19-Jul-2021					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
RD1_GAIN		Before	1	0.85	1.02095	1.15	<div><div></div><div></div><div></div><div></div><div></div></div>
RD2_GAIN		Before	1	0.85	1.02497	1.15	<div><div></div><div></div><div></div><div></div><div></div></div>

RD3_GAIN		Before	1	0.85	1.05785	1.15	<div><div></div><div></div><div></div><div></div><div></div></div>
RD4_GAIN		Before	1	0.85	1.05809	1.15	<div><div></div><div></div><div></div><div></div><div></div></div>
RD1_OFFSET	in	Before	0	-2.2	-0.78812	2.6	<div><div></div><div></div><div></div><div></div><div></div></div>
RD2_OFFSET	in	Before	0	-2.2	0.026194	2.6	<div><div></div><div></div><div></div><div></div><div></div></div>
RD3_OFFSET	in	Before	0	-2.2	-1.02032	2.6	<div><div></div><div></div><div></div><div></div><div></div></div>
RD4_OFFSET	in	Before	0	-2.2	-0.6299	2.6	<div><div></div><div></div><div></div><div></div><div></div></div>

## PPC Caliper Calibration - PPC Accumulations

Before (Manual Entry): 19:53:08 19-Jul-2021

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div><div></div><div></div><div></div></div>
Caliper 1 Zero Radius - 0	in	Before	----	----	----	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Caliper 2 Zero Radius - 0	in	Before	----	----	----	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Caliper 3 Zero Radius - 0	in	Before	----	----	----	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Caliper 4 Zero Radius - 0	in	Before	----	----	----	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Caliper 1 Plus Radius - 0	in	Before	----	----	----	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Caliper 2 Plus Radius - 0	in	Before	----	----	----	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Caliper 3 Plus Radius - 0	in	Before	----	----	----	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Caliper 4 Plus Radius - 0	in	Before	----	----	----	----	<div><div></div><div></div><div></div><div></div><div></div></div>

## EDTC-B (Enhanced Digital Telemetry Cartridge - Version B) Calibration - Run 1A

Primary Equipment :	EDTC-B	EDTC-B	9316
Calibration Parameter :	Plus Reference (Jig minus background reference)	165	

## EDTC-B Accelerometer Calibration - EDTC-B Accelerometer Calibration

Before:

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div><div></div><div></div><div></div></div>
AZ Vertical Measurement - 0	ft/s2	Before	----	----	----	----	<div><div></div><div></div><div></div><div></div><div></div></div>

## EDTC-B Memory Data - EDTC-B Memory Data

Master (EEPROM): 07:33:58 19-Jul-2021

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div><div></div><div></div><div></div></div>
Initial PMT HV	V	Master	----	----	1368.000	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Serial Number		Master	----	----	1578	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 0		Master	----	----	2.946E+000	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 1		Master	----	----	2.708E-004	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 2		Master	----	----	3.975E-007	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 3		Master	----	----	-5.664E-008	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 4		Master	----	----	1.326E-009	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 5		Master	----	----	-9.924E-012	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 6		Master	----	----	2.514E-014	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 7		Master	----	----	-5.486E-003	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 8		Master	----	----	4.410E-005	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 9		Master	----	----	-2.638E-008	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 10		Master	----	----	1.522E-010	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Accelerometer Coefficients - 11		Master	----	----	-1.560E-012	----	<div><div></div><div></div><div></div><div></div><div></div></div>
Gamma-Ray Detector Serial Number		Master	----	----	79527	----	<div><div></div><div></div><div></div><div></div><div></div></div>

## EDTC-B Gamma-Ray Calibration - Gamma Ray Coefficients

Before (Measured): 19:36:57 17-Jul-2021

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div><div></div><div></div><div></div></div>
Gamma Ray Gain		Before	1.000	0.900	1.044	1.100	<div><div></div><div></div><div></div><div></div><div></div></div>

## EDTC-B Gamma-Ray Calibration - Gamma Ray Accumulations

Before (Measured): 19:36:57 17-Jul-2021

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div><div></div><div></div><div></div></div>
RGR Zero Measurement	gAPI	Before	----	0	77.309	120.000	<div><div></div><div></div><div></div><div></div><div></div></div>
RGR Plus Measurement	gAPI	Before	165.000	150.000	157.995	180.000	<div><div></div><div></div><div></div><div></div><div></div></div>



Company:	University Of Utah	Schlumberger
Well:	FORGE 78B-32	
Field:	None	
County:	Beaver	
State:	Utah	

# Borehole Profile Log