



Land Based Recorder



Cable-free, Radio-free, Autonomous Data Recorder

- Scalability greater than 50,000 channels
- Delivers high-resolution with a 24-bit delta-sigma ADC
- Built-in GPS receiver and disciplined clock
- Greater than 30 days of continuous recording
- Compatible with explosive, vibratory, and impulsive energy sources
- Accepts standard analog sensor inputs
- Has a built-in full-resolution test generator
- Available as 1, 2, 3, or 4 channel versions
- Has an LED Status/Deployment state indicator

Cable-free, Radio-free Autonomous Data Recording

The GSX is designed for cable-free/radio-free seismic data recording. The self-contained unit includes 1 to 4 channels of 24-bit digitization, an integrated high sensitivity GPS receiver, built-in test signal generator, up to 32 GB per channel of non-volatile solid-state data storage, and a high-speed data port. The unit is housed in a sealed case, with an input connector and an extended life battery/data port connector.



GSX System Tests

The seismic channel performance and sensor tests can be performed by the GSX System. The user can choose a partial or complete set of tests that can be run in sequence. The user can also choose to display all of the results or only the failures. In the tests described below, the system software automatically controls the Channel Input Switch Positions and Test Oscillator Settings during the tests. All tests can be run at all sample intervals and preamp gains of the GSX.

- | | |
|--------------------------------------|------------------------------|
| ▲ Harmonic Distortion | ▲ Gain Accuracy |
| ▲ Impulse Response | ▲ Common Mode Rejection |
| ▲ Equivalent Input Noise | ▲ Geophone Impedance and THD |
| ▲ Instantaneous System Dynamic Range | ▲ Crossfeed (multi-channel) |

FEATURES AND SPECIFICATIONS

- 24-bit digital recorder
- Built-in GPS and disciplined clock
- Built-in full resolution test signal generator
- Solid-state flash memory
- Scalability greater than 50,000 channels
- Greater than 30 days of continuous recording
- Compatible with vibratory, explosive, and impulsive energy sources
- LED Status/Deployment State Indicator
- Accepts standard analog sensor input
- Available as 1,2,3, or 4 channel versions
- 24-bit delta-sigma ADC
- 1 Hz to 1600 Hz freq. response
- <20 μ sec. of UTC (GPS clock)
- Up to 32 GBytes per channel flash memory storage
- External extended life battery
- Operating Temperature: -40° C to $+85^{\circ}$ C
- Humidity: 0 to 100%
- Selectable Gains:
 - X1, X2, X4, X8, X16, X32, X64
 - 0, 6, 12, 18, 24, 30, 36 dB
- Sample Intervals:
 - .25, .5, 1, 2, 4 milliseconds

Max Input Signal:	1.80 Vrms @ 0 Gain
Total Dynamic Range:	140 dB
System Dynamic Range @ 0dB Gain:	
	126 dB @ 4 msec SI
	124 dB @ 2 msec SI
	120 dB @ 1 msec SI
	117 dB @ .5 msec SI
	106 dB @ .25 msec SI
Equivalent Input Noise @ 2 msec SI:	
	1.13 μ V @ Gain 0 dB
	0.58 μ V @ Gain 6 dB
	0.33 μ V @ Gain 12 dB
	0.22 μ V @ Gain 18 dB
	0.19 μ V @ Gain 24 dB
	0.18 μ V @ Gain 30 dB
	0.17 μ V @ Gain 36 dB
Input Impedance:	
	20 k Ω /0.06 μ f Difference Mode
	205 k Ω Common Mode

System Dynamic Range @ 2 msec SI:	
	124 dB @ Gain 0 dB
	123 dB @ Gain 6 dB
	122 dB @ Gain 12 dB
	120 dB @ Gain 18 dB
	115 dB @ Gain 24 dB
	110 dB @ Gain 30 dB
	105 dB @ Gain 36 dB
Total Harmonic Distortion:	0.0005%
Common Mode Rejection:	0.001%
Gain Accuracy:	1%
Anti-Alias Filter:	
	Rejection @ Nyquist: 130 dB
	Frequency @ -3 dB: 0.83 Nyquist
	Linear or Minimum Phase
GPS Time Standard:	<1 ppm
Weight:	2 lbs.
Max Dimensions:	3.5"W x 3.0"H x 6.67"L

Big Advances in Small Packages



GSX1 with a BN6 battery and a GS-ONE geophone in a Land Case.



Geospace Technologies, Canada
2735 - 37th Avenue N.E.
Calgary, Alberta,
T1Y 5R8 Canada
403 250-9600

Geospace Technologies, China
Room 700, 7th Floor
Lido Office Tower, Lido Place
Jichang Road, Jiang Tai Road
Beijing, 100004, P.R.China
011 (86) 10 6437 8768

Geospace Technologies
Sucursal Sudamericana
Carrera 127-22 G 28 Int. 30
Agrupación Industrial La Esperanza
Bogotá, Colombia
011-57-1-742-7414

Geospace Technologies, Eurasia
Kirovogradskaya, 36
Ufa, Baskortostan
Russia 450001
011 (7) 3472 25 39 73



Geospace UK
F3 Bramingham Business Park,
Enterprise Way, Luton
Bedfordshire LU3 4BU, England
011 44 (0) 7775 688 467

7007 Pinemont Drive • Houston, Texas 77040 USA

www.geospace.com

Tel: 713-986-4444 • Fax: 713-986-4445