

GENERAL INFORMATION

CUSTOMER	FORGE UTAH	WELL
DATE	6/15/2023	REPORT NUMBER 70
RIG / TYPE	Frontier 16	LAST CASING 11.75" Int csng
RKB ELEVATION	5447.65'	LAST CASING SHOE (FT MDRT) 4839' MD
SPUD DATE	4/26/2023	LAST SURVEY (MD/INC/AZI)) 10165' MD/INC 65.97/AZI 103.61
MIDNIGHT DEPTH (FT MDRT)	10460' MD	COMPANY REPRESENTATIVES Leroy Swearingen/Brian Gresham
PREVIOUS MIDNIGHT DEPTH (FT MDRT)	10460' MD	MUD LOGGERS A.T. Kuhns/Jack Breland
24 HRS PROGRESS (FT)	7' FT	SAMPLE CATCHERS E Salinas/L Rodriguez
Current Hole Depth (FT)	10482' MD	

GENERAL MUD INFORMATION

MUD TYPE	WBM	ECD (PPG)	----
MW IN (PPG)	8.4	MUD PIT TEMPERATURE (deg C)	
MW OUT (PPG)	8.4	FLOW LINE TEMPERATURE (deg C)	

DRILLING PARAMETERS (PREVIOUS DRILLING)

PARAMETER	DEPTH	MAXIMUM	AVERAGE
ROP	10474' MD	2.2 FT/HR	.95 FT/HR
WOB	10480' MD	15.3K	12.5K
SPP	10470' MD	595	482
FLOW IN	10469' MD	36.10%	33.80%

LITHOLOGY

FROM / TO DEPTH	Description
First Sample On Tour 10480' MD	GNEISS: QTZ, CLR, TRANSL, FRSTD, PRED F-MED GRN, ANG-SBANG, HD-MOD HD, FLDSPR: WH, OPQ, SBANG-SBBLKY, SUC TXT, BIOTITE, MAGNETITE, TR HRNBLNDE, CHLORITE IP, EPIDOTE IP, TR SERICITE, TAN – LHT BRN CLAY.
12:00 Sample 10480' MD	SAA
Last Sample Before Report 10480' MD	SAA

DRILL EVENTS

LAST 24 HOURS OPERATION SUMMARY	TIH W/CLEANOUT ASSEMBLY. DRILLED 2 FEET OF FORMATION. POOH. TIH W/CORE ASSEMBLY #9. STARTED CORE DRILLING @ 0024 HRS ON 6/15/23.
06:00 - 04:00 OPERATION SUMMARY	CORE #9 DRILLING OPERATIONS: 0315 HRS DEPTH 10480
CUT OFF FOR REPORT @ 0330HRS	
NEXT 24 HOURS OPERATION	CORE DRILL FOR CORE #9. PULL CORE OUT OF HOLE.