

GENERAL INFORMATION

CUSTOMER	FORGE UTAH	WELL	
DATE	5/17/2023	REPORT NUMBER	19
RIG / TYPE	Frontier 16	LAST CASING	16" Surface csng
RKB ELEVATION	5447.65'	LAST CASING SHOE (FT MDRT)	4839' MD
SPUD DATE	4/26/2023	LAST SURVEY (MD/INC/AZI)	4742' MD/INC 2.12/AZI 121.07
MIDNIGHT DEPTH (FT MDRT)	6545'	COMPANY REPRESENTATIVES	Leroy Swearingen/Brian Gresham
PREVIOUS MIDNIGHT DEPTH (FT MDRT)	6142'	MUD LOGGERS	A.T. Kuhns/Jack Breland
24 HRS PROGRESS (FT)	0'	SAMPLE CATCHERS	E Salinas/L Rodriguez
Current Hole Depth (FT)	6545'MD		

GENERAL MUD INFORMATION

MUD TYPE	WBM	ECD (PPG)	----
MW IN (PPG)	8.3+	MUD PIT TEMPERATURE (deg C)	
MW OUT (PPG)	8.3+	FLOW LINE TEMPERATURE (deg C)	

DRILLING PARAMETERS

PARAMETER	DEPTH	MAXIMUM	AVERAGE
ROP	6483'MD	70.2	40.2
WOB	6248'MD	61.8	32.5
SPP	6545'MD	1212	1160
FLOW IN			

LITHOLOGY

FROM / TO DEPTH	Description
First Sample On Tour NO Drilling	
12:00 Sample NO Drilling	
Last Sample Before Report NO Drilling	

DRILL EVENTS

LAST 24 HOURS OPERATION SUMMARY	Drilled ahead to 6545'MD. Recovered particle drilling pellets, shards, grit size steel. Circulated hole to clean. POOH (BHA). TIH TO 10' PASSED SHOE. PUMP 2-49 BRLS OF WALNUT SWEEPS. TIH
06:00 - 04:00 OPERATION SUMMARY	TIH TO 10' PASSED SHOE. PUMP 2-49 BRLS OF WALNUT SWEEPS. TIH TO 5700' MD
NEXT 24 HOURS OPERATION	Finish TIH. Drill ahead w/Production Curve Assembly