

GENERAL INFORMATION

CUSTOMER	FORGE UTAH	WELL
DATE	5/29/2023	REPORT NUMBER 39
RIG / TYPE	Frontier 16	LAST CASING 16" Surface csng
RKB ELEVATION	5447.65'	LAST CASING SHOE (FT MDRT) 4839' MD
SPUD DATE	4/26/2023	LAST SURVEY (MD/INC/AZI) 4742' MD/INC 2.12/AZI 121.07
MIDNIGHT DEPTH (FT MDRT)	9800'	COMPANY REPRESENTATIVES Leroy Swearingen/Brian Gresham
PREVIOUS MIDNIGHT DEPTH (FT MDRT)	9800'	MUD LOGGERS A.T. Kuhns/Jack Breland
24 HRS PROGRESS (FT)	0'	SAMPLE CATCHERS E Salinas/L Rodriguez
Current Hole Depth (FT)	9800' MD	

GENERAL MUD INFORMATION

MUD TYPE	WBM	ECD (PPG)	---
MW IN (PPG)	8.4	MUD PIT TEMPERATURE (deg C)	
MW OUT (PPG)	8.4	FLOW LINE TEMPERATURE (deg C)	

DRILLING PARAMETERS (PREVIOUS DRILLING)

PARAMETER	DEPTH	MAXIMUM	AVERAGE
ROP	9701'MD	375 ft/hr	204 ft/hr
WOB	9464'MD	75.2 klb	69.8 klb
SPP	9675'MD	2836 psi	2259 psi
FLOW IN	9770'MD	39.90%	39.00%

LITHOLOGY

FROM / TO DEPTH	Description
First Sample On Tour NA	NO DRILLING ON THIS TOWER
12:00 Sample NA	
Last Sample Before Report NA	

DRILL EVENTS

LAST 24 HOURS OPERATION SUMMARY	WIRELINE GYRO LOGS. POOH: P/U CORING BARREL, TIH TO DRILL CORE #1 9800'MD - 9860'MD
06:00 - 04:00 OPERATION SUMMARY	POOH: BRAKE OFF BIT AND BIT SUB. STAGE OUT CORING TOOLS. P/U CORING BARREL, TIH TO DRILL CORE #1 9800'MD - 9860'MD
CUT OFF FOR REPORT @ 0330HRS	
NEXT 24 HOURS OPERATION	POOH, REAM CORE #1 DRILL AHEAD TO CORE #2