

GENERAL INFORMATION

CUSTOMER	FORGE UTAH	WELL	
DATE	5/19/2023	REPORT NUMBER	22
RIG / TYPE	Frontier 16	LAST CASING	16" Surface csng
RKB ELEVATION	5447.65'	LAST CASING SHOE (FT MDRT)	4839' MD
SPUD DATE	4/26/2023	LAST SURVEY (MD/INC/AZI)	4742' MD/INC 2.12/AZI 121.07
MIDNIGHT DEPTH (FT MDRT)	6950'	COMPANY REPRESENTATIVES	Leroy Swearingen/Brian Gresham
PREVIOUS MIDNIGHT DEPTH (FT MDRT)	6545'	MUD LOGGERS	A.T. Kuhns/Jack Breland
24 HRS PROGRESS (FT)	405'	SAMPLE CATCHERS	E Salinas/L Rodriguez
Current Hole Depth (FT)	6950'MD		

GENERAL MUD INFORMATION

MUD TYPE	WBM	ECD (PPG)	----
MW IN (PPG)	8.3+	MUD PIT TEMPERATURE (deg C)	
MW OUT (PPG)	8.3+	FLOW LINE TEMPERATURE (deg C)	

DRILLING PARAMETERS

PARAMETER	DEPTH	MAXIMUM	AVERAGE
ROP	NO DRILLING THIS TOUR		
WOB			
SPP			

FLOW IN

LITHOLOGY

FROM / TO DEPTH	Description
First Sample On Tour 6770'MD	NO DRILLING THIS TOUR
12:00 Sample N/A	SAA
Last Sample Before Report N/A	SAA

DRILL EVENTS

LAST 24 HOURS OPERATION SUMMARY	Drill string pu to 6436'MD, running SCIENTIFIC GYROSCOPE to TD. Complete gyroscope run Rig Down Scientific. RIH to bottom. Kick off drilling 13:05 @ 6545'MD. Drill to 6777 @ 13:25. PU off btm and circ, wo encoder replacement. BOB drilling: 6777'MD at 18:29. Ceased drilling: 6950'MD at 23:48 18 May. Condition wellbore and TOOH for OH logging.
06:00 - 03:30 OPERATION SUMMARY	SLB on location. OH logging commenced.
NEXT 24 HOURS OPERATION	Complete OH Logging. RIH to drill 500'. TOOH for insulated DP testing.