

GENERAL INFORMATION

CUSTOMER	FORGE UTAH	WELL
DATE	7/16/2023	REPORT NUMBER 125
RIG / TYPE	Frontier 16	LAST CASING 11.75" Int csng
RKB ELEVATION	5447.65'	LAST CASING SHOE (FT MDRT) 4839' MD
SPUD DATE	4/26/2023	LAST SURVEY (MD/INC/AZI)) 10165' MD/INC 65.97/AZI 103.61
MIDNIGHT DEPTH (FT MDRT)	10947' MD	COMPANY REPRESENTATIVES Leroy Swearingen/Brian Gresham
PREVIOUS MIDNIGHT DEPTH (FT MDRT)	10947' MD	MUD LOGGERS A.T. Kuhns/Reed Barrett
24 HRS PROGRESS (FT)	0 FT	SAMPLE CATCHERS Nash Cantwell
Current Hole Depth (FT)	10947' MD	

GENERAL MUD INFORMATION

MUD TYPE	WBM	ECD (PPG)	----
MW IN (PPG)	8.4	MUD PIT TEMPERATURE (deg C)	
MW OUT (PPG)	8.4	FLOW LINE TEMPERATURE (deg C)	

DRILLING PARAMETERS (PREVIOUS DRILLING)

PARAMETER	DEPTH	MAXIMUM	AVERAGE
ROP	NO DRILLING THIS TOUR		
WOB			
SPP			
FLOW IN			

LITHOLOGY

FROM / TO DEPTH	Description
First Sample On Tour 10947' MD	NO DRILLING THIS TOUR
12:00 Sample 10947' MD	
Last Sample Before Report 10947' MD	

DRILL EVENTS

LAST 24 HOURS OPERATION SUMMARY	R/U BOP tester, Test BOP @ 250 psi low 6000 psi high 10 min hold, R/U rotating head clamp, stab rubber, install trip nipple R/U old rotating head, load collars on racks, get strap, wait on fiber optic to finish uplinks, P/U bit sub reamer 24 collars 36 joints, DP trip in 30 stands from derrick. grease blocks, top drive, swivel packing, drawworks, strap pipe
0600 - 1600 OPERATION SUMMARY	Circulate, P/U DP F/4750' MD T/7000' MD, Circulate & strap pipe, P/U DP F/7000' MD T/9900' MD, tag up float collar @9934' MD, Drill out float collar and shoe track
NEXT 24 HOURS OPERATION	Drill out bentonite plug, trip