

GENERAL INFORMATION

CUSTOMER	FORGE UTAH	WELL
DATE	5/31/2023	REPORT NUMBER 44
RIG / TYPE	Frontier 16	LAST CASING 11.75" Int csng
RKB ELEVATION	5447.65'	LAST CASING SHOE (FT MDRT) 4839' MD
SPUD DATE	4/26/2023	LAST SURVEY (MD/INC/AZI)) 9709' MD/INC 64.81/AZI 107.357
MIDNIGHT DEPTH (FT MDRT)	9817'	COMPANY REPRESENTATIVES Leroy Swearingen/Brian Gresham
PREVIOUS MIDNIGHT DEPTH (FT MDRT)	9817'	MUD LOGGERS A.T. Kuhns/Jack Breland
24 HRS PROGRESS (FT)	0'	SAMPLE CATCHERS E Salinas/L Rodriguez
Current Hole Depth (FT)	9817' MD	

GENERAL MUD INFORMATION

MUD TYPE	WBM	ECD (PPG)	----
MW IN (PPG)	8.4	MUD PIT TEMPERATURE (deg C)	
MW OUT (PPG)	8.4	FLOW LINE TEMPERATURE (deg C)	

DRILLING PARAMETERS (PREVIOUS DRILLING)

PARAMETER	DEPTH	MAXIMUM	AVERAGE
ROP			
WOB			
SPP			
FLOW IN			

LITHOLOGY

FROM / TO DEPTH	Description
First Sample On Tour NA	No Drilling this Tour
12:00 Sample 9810'	
Last Sample Before Report 9810'	

DRILL EVENTS

LAST 24 HOURS OPERATION SUMMARY	P/U CORING BARREL, TIH & DRILLED CORE #1 9800'MD - 9817'MD. POOH @ 2325 HRS. Mark, cut and prepare core specimen for shipment. TIH with bit and drill string. Performed wireline GYRO run. Started POOH @ 0205 hrs.
06:00 - 04:00 OPERATION SUMMARY	TIH with insert bit to clean out 8.75" hole. @1530: bit depth 9770'md and circulating
CUT OFF FOR REPORT @ 0330HRS	
NEXT 24 HOURS OPERATION	Clean up Core Section:TOOH to Prepare for Coring Operations for Core#4