

MANSFIELD HOME - CONSTRUCTION SPECIFICATIONS

Builder Clearview Properties, LLC 1037 Hinesburg Road, Suite A South Burlington, VT 05403 Homeowner/Project

Clearview #

Specification Date: Site Plan Date: Plan Date: Electric Plan:

Mansfield Plan: Two story home with unfinished lower level. Two floors of finished area with approximately 1,568 square feet of living space; 784 square feet of unfinished Lower Level, 484 square foot 2-car garage, and a 60 square foot front porch.

Location Total Square Feet
First Floor 784
Second Floor 784

Total Finished Square Feet 1,568
Lower Level 784
Garage 484
Front Porch 60

Personal Choice Lists PCL# **Color Code** Date **GRAPE ORANGE GOLD GREEN BLUE PURPLE** PINK **HUNTER SKY BLUE LAVENDER BROWN NAVY CRANBERRY AQUA PEACH**

Specification and Appendix Approval

RED

Appendix A: Window Schedule
Appendix B: Exterior and Interior Door Schedule
Appendix C: Lighting Schedule
Appendix D: Plumbing Schedule
Appendix E: Finish Hardware Schedule
Appendix F: Flooring Schedule
Appendix G: Appliance Schedule



	MANSFIELD HOME - CONSTRUCTION SPECIFICATIONS	
Section	Information	Image
Permits		
	Builder responsible to obtain all necessary permits including:	
	- Soil Erosion and Sediment Control	
	- Zoning	
urveys		
	Home is to be staked by builder	
ite Clearing		
<u> </u>	Builder is responsible for all site clearing, as needed	
Itilities Connections		
	Builder responsible for all site work and site balance to include	
Water	Connection to City of Milton water system	
Sewer	Connection to City of Milton sewer system	
Gas	Connection to Natural Gas lines at road.	
Power	Underground power	
Cable	Cable TV conduit to house	
Cabic	All excavation, fill and labor is included	
nergy Package	allows allowly in what to interese	
	Home to be built to VT Residential Building Energy Standards (RBES)	
	Compliant with Act 250 Stretch Code	
Home to Include	Compliant with Act 250 Stretch code	
nome to merade	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light.	
	Vented to the outside	
	Additional caulking and air sealing of joists to reduce air infiltration into the home, including	
	shoe plate; windows; and where wires and pipes go to cold spaces	
	R-15 Rigid Thermax insulation on Interior of Lower Level - floor to top of concrete wall	
	Selected use of closed cell foam to improve overall air sealing of attic in home	
	Blower Door Test as home completed required for VT RBES	
Solar Prep	Home solar ready with conduit running from LL up to Attic Space	
oundation	Home solal ready with conduit running from LE up to Attic Space	
	Poured Concrete	
Type Wall Height	7'10"	
Wall Height Lookout Height		
	4' Frost Wall Min. 2000 PSL @2 days with steel reinforcement	
Strength	Min. 3000 PSI @2 days with steel reinforcement Continuous 8" x 16" reinforced	
Footer lat Work Concrete	Continuous 8 x 10 Tellillorceu	
	Poured Concrete	
Lower Level		
Finish	Smooth	
"Keyway" Joints	Saw cut	
Thickness	-	
Strength	House: Min. 3000 PSI @ 28 days Garage: Min. 4000 PSI @ 28 days	
Moisture Barrier	Tarred damp proofing membrane sprayed on exterior of foundation walls.	
	6 mil poly under concrete house slab.	
Constant	Footing drains installed below footers around Lower Level and drained to daylight in back yard.	
Ground water controls	Drain tile buried in clean stone; covered with mirafi fabric; clean sand fill against foundation. Site	
	graded to shed surface water away from house.	
Rock Wall	Boulder rock walls as needed for the grading of the yard.	
	Boulders from the site are machine-placed to create walls.	
Lower Level Slab Plumb	Available as an Option	



Driveway/Entrance		
Diversal, Entrance	12" thick gravel two car driveway on top of mirafi fabric.	
Drive	Driveway to be finish paved with 2" of compacted asphalt.	
	briveway to be mish paved with 2. Or compacted aspiralt.	
Walkway	42" Sidewalk from front porch to driveway	
Frame		
Exterior Walls	2x6 SPF 24" o.c.	
Interior Walls	2x4 SPF 24" o.c.	
Plate Height	9'-1" on first floor; 8'-1" on second floor and 7'10" in lower level	
Plate	2x6 treated southern yellow pine with foam sill seal	
Floor Framing	2x10 SPF 19.2" o.c.	
Sub Flooring	3/4" 4x8 T&G OSB glued and nailed	
	2 or 3 ply 2x12, nailed and glued, as specified by engineering load design, supported by 3-1/2"	
Girders	concrete filled lally columns in Lower Level	
Sheathing	7/16" 4x8 OSB	
Roof	Pre-engineered roof trusses 24" o.c. 5/8" T&G OSB rated sheeting	
Roof Pitch	Pitches: 7/12 at Main House; 12/12 at Garage; 6/12 at Front Porch	
House Wrap	Professional house wrap with flashing around all windows and doors	
Roofing	Frotessional nouse with maximig around all willdows and doors	
Roomig		
	Ice and water shield on eaves and valleys. Vented on ridge to achieve proper ventilation.	
Underlayment	Owens Corning ProArmor Synthetic Roof Underlayment	
Shingles	Owens Corning TruDefinition Shingles Limited Lifetime Warranty	
Color	To be selected by Owner	
Siding/Exterior Elements		
Siding	Norandex Woodsman Select	
Gable Ends	Double 4" Color to selected by owner	
Clapboard	Double 4", Color to be selected by owner	
Board and Baton	None	
Eaves	Two piece aluminum wrapped - White	
Soffit	Perforated soffit for proper venting	
Corners	6" White Vinyl Corners with Foam Backer	
Trim Details	Frieze board and Garage Door Trim to be PVC	
Drip Edge	Galvanized	
Shutters	Available as Option	
Gutters & Downspouts	Available as option	
Gutters & Downspouts	White Seamless Gutters	
Windows	White Seamess dutiers	
	See Appendix A: Window Schedule	
Brand	Harvey Slimline	
Color	White	
Construction	Vinyl, Low-E, Insulated Double-Pane	
Exterior Casing	J Channel Only (Brickmould)	
U-Factor	0.30	
Grills	Grills Between Glass 6 over 0	
Screens	Fiberglass Mesh	
Exterior Doors		
	See Appendix B: Exterior and Interior Door Schedule	
Brand	Therma-Tru	
Color	See Exterior Paint Section	
Construction	Insulated Fiberglass	
Exterior Casing	5/4x4 Flat	
Storm Doors	None	
3(3)111 20013	1.10.10	



Overhead Garage Doors		
Model	8300 Series Insulated Steel Door	
Size	16' x 7'	
Design	Colonial Raised Panel Door	
Color	Manufacturer White	
Opener	8" lift master 1/2 horsepower electric opener	
Remotes	2 remotes included	
Frame Key Pad	Keyless entry punch pad	
Decks & Porches	ncyress critiy purion pau	<u> </u>
Covered Entry Porch		
Porch Framing	6' x 10' framed with PT 2x8 joists	
Decking	5/4x6 PT decking	
Posts	PVC wrapped and PT 6x6 Posts, 2x8 roof beams - White. Posts wrapped top and bottom.	
	1 1 1	
Roof	Roof to be truss framed, roof shingles to match house	
Ceiling	White vinyl bead board	
Stairs	Stairs from porch to walkway to be PT box steps with 5/4x6 PT treads.	
Rail	Available as an Option	
Finish	Porch posts, beams - White CPVC Trim	
Color	Porch decking, stair tread, risers and PT Rim stained with Total Wood Preservative - Selected by	
Color	Owner	
Deck	14' x 12' Deck Available as Option	
Exterior Paint		
Exterior Doors - Excluding Front Door	Painted Satin Finish, White	
Exterior Trim - Including Frieze Board and Door Surrounds	Painted Satin Finish, White	
Front Door	2 coats Exterior Paint, Color to be Selected by Owner	
Sidelight	2 coats Exterior Paint, Color to be Selected by Owner	
Front Porch Rail	Available as an Option	
Front Porch Posts	CPVC Wrapped, White	
Front Porch Roof Beams	CPVC Trim, White	
Front Porch Rim board	Stained. Color to be Selected by Owner.	
Front Porch Stair Risers	Stained. Color to be Selected by Owner. Stained. Color to be Selected by Owner.	
Front Porch Decking Electrical & Low Voltage	Stained. Color to be Selected by Owner.	
Electrical & Low Voltage	Underground electrical service, 40 circuit 150 AMP Panel with Surge Protection. Open double	
	slot for future solar.	
Plugs and Switches		
Switch Style	Toggle	4
Plate Style	Toggle screw on plates	
Switch Color	White	33
Dimmers	Available as Option	l l
Exterior Plugs	Per Electrical Plan	Ф
Lighting		
Lighting Fixtures	See Lighting Finish Schedule (Appendix C: Light Fixtures Schedule)	
Recessed Lights	None	
Under Cabinet Lighting	Available as Option	
Miscellaneous	/ transact as Option	
IVIISCEIIAIIEOUS	GFI protection for all interior and exterior 240-volt outlets. 120 volt outlets in future finished	
Outlets		
Door Chima	areas of basement. Minimum of 2 Island Outlets. Per Electrical Plan.	
Door Chime	Nutone BK125LWH: One 2-note, white door chime	
Smoke/CO2	1 CO/Smoke per floor (2 Total), 1 Smoke per bedroom (3 Total) - Kidde 120V Intelligent 10 Year	
<u> </u>	Lithium Battery Smoke Alarm Model P4010ACS	
Bath Vents	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM	
Paddle Fan Boxes	Paddle fan rated boxes in all Bedrooms, Dining room, and Living room	
Cat 5 (data/phone)	Yes, per electrical plan	
Coax Cable	Yes, per electrical plan	
Security/Surveillance	None	
Central Vacuum	None	
Audio	None	
Solar Prep	Conduit running from LL up to Attic Space	



Light Fixtures		
	See Appendix C: Light Fixture Schedule	
	Plumbing	
leating and Venting		
Furnace	Ducane - 96G2UH045BV12	
Furnace Size	40,000 BTU	
Efficiency Rating	96%	
Zones	Zone 1: First Floor and Second Floor	72
Second Zone	Available as Option	
Air Conditioner	Available as Option	
Thermostat	Ecobee Thermostat; First Floor and Second Floor	
Bath Venting	Panasonic WhisperLite™ Fan/Light - Quiet, Spot Ventilation Solution, 110 CFM Bath Fan/Light.	
Batti Veriting	Vented to the outside	
Dryer Venting	Microwave/Hood Vent vented to the outside	
as		
Main Kitchen Range	Yes	
Main Fireplace	Available as Option	
Dryer	No	
Furnace	Yes	
Hot Water System	Hybdid Electric	
Grill Line at Deck	Available as Option	
ireplace and Mantle		
Fireplace in Living Room	Available as Option	
lumbing Fixtures		
	See Appendix D: Plumbing Schedule	
liscellaneous Plumbing		
Outdoor Faucets	2 Frost-Free Hose Bibs, located at back of the main house and on the side of the front porch	
Hot Water Heater	State 50 Gallon Hybrid Electric water heater	
Laundry	Washer Box Valve with single handle shutoff and drain; appliances pricing optional	
	PVC Drainage plumbing.	
Plumbing	PEX continuous piping for all domestic water.	
	All plumbing installed according to National Plumbing Code by licensed plumber.	
Dodos	Radon Piping runs from under Lower Level concrete slab through roof.	
Radon	This is a passive system, no fan.	
Utility Sink	Available as Option	



	Cabinets & Countertops	
Cabinets		
Kitchen		
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Kitchen Island		
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Owner's Bath		
Size	72" Vanity with 2 bowls	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Bath #2		
Size	60" Vanity with single bowl	
Brand	Fabuwood Galaxy/Allure Series	
Style	Full Overlay Doors	
Color	Color to be determined by Owner	
Countertops		
Kitchen		
Style	Classic Series Quartz	
Color	To Be Selected by Owner	
Edge Detail	Pencil Edge	to d M II
Cut-Outs	Under Mount Sink	
Backsplash	4" Classic Series Quartz	
B/S Location	Perimeter Back Only	
Kitchen Island		
Style	Classic Series Quartz	
Color	To Be Selected by Owner	
Edge Detail	Pencil Edge	
Cut-Outs	None	Kitchen Tops (not color or Style)
Owner's Bath		
Style	Cultured Marble with 2 integrated flush rectangle bowls	31
Color	Cotton White	Me
Edge Detail	Square Edge	MIC
Cut-Outs	None	H. C.
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	
Bath #2		
Style	Cultured Marble with 1 integrated flush rectangle bowls	
Color	Cotton White	
Edge Detail	Square Edge	
Cut-Outs	None	
Back Splash	4" integral Cultured Marble	
B/S Location	Back Only	



	W 11.2 = 1 · · · · · · = · · · · · · · ·	777257772
	Wall & Trim Interior Detail Work	
Insulation		
Exterior Walls	R-21 6" Fiberglass Batts with Poly Vapor Barrier	
Interior Walls	R-13 3-1/2" Fiberglass Batts for bath walls (Soundproofing)	
Rigid Insulation	Box sill in first and second floor joists insulated with rigid insulation	
Attic	R-60 Cellulose with backer boards at eves for ventilation	
Garage	Not insulated	
Foundation	2-1/2" R-15 Thermax glued to concrete wall	
Drywall		
Living area walls	1/2" Sheet Rock, taped with 3 coats of joint compound at walls and ceilings	
Ceilings	Smooth Finish, minor shadow variations are possible in ceilings	
Garage	Unfinished	
Trim Details	<u></u>	
Casing	2-1/2" Colonial Casing	
Base	3-1/2" Colonial Base Board	
Wainscot	+/-60" High Wainscot at Mudroom under Black Metal Coat Hooks, 40" High in Powder Room	
Crown	Available as Option	
Built - Ins		
	Black Metal Hooks at Mudroom	2
Mirrors		
Owners Bath	Plate Glass mirror with ground edge, no bevel	
Bath #2	Plate Glass mirror with ground edge, no bevel	
Powder Room	By Owner	
Interior Stairs/Railing		
Main to Second Floor	Carpet Grade Stairs	
	First Floor to Landing to be half wall with a hardwood cap and railing on wall. Cap to be Maple,	
	sealed Natural.	
	Rail on wall stained	
Main to Lower Level	Carpet Grade Stairs	
	Rail on wall stained	
Handrail Brackets	Satin Nickel	Marie Control of the
Closet Shelving		
	All closets systems will be vented wire and the system is indicated on the plan.	
	See Closet Plan for Details.	
Interior Paint		
Dainted Interior Wells	1 coat primer	
Painted Interior Walls	2 coats Low VOC Flat Latex Paint, Color to be selected by owner, OK to Color Match	
Accent Wall	None	
Ceilings	To match walls	
	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
Interior Trim	Color to be selected by owner, OK to Color Match	
Mainagt	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
Wainscot	Color to be selected by owner, OK to Color Match	
Interior Done	Painted, 1 coat primer, 2 coats Semi-Gloss Latex Paint,	
Interior Doors	Color to be selected by owner, OK to Color Match	
Fireplace Mantle (optional)		
	Rail and Newel Sealed and Matching Wood Floor	
Main to Second Floor Stairs	Baluster Posts Painted to Match Interior Trim	
Main to Lower Level Stairs	Stained railing to Match Wood on First Floor	
Main to Lower Level Stairs	Stained railing to Match Wood on First Floor	



Interior Doors		
	See Door Appendix B: Exterior and Interior Door Schedule	
Finish Hardware	·	
	See Appendix E: Finish Hardware Schedule	
Flooring	·	
	See Appendix F: Flooring Schedule	
Appliances		
	See Appendix G: Appliance Schedule	
Landscaping		
	All disturbed portions of yard to be seeded.	
Lawn	Lawn area will generally include front yard, side yard and rear yard.	
	Lawn area to be covered with approximately 4" of native topsoil.	
8 Foundation Shrubs	To be Selected by Owner, See Landscape Plan	
8 Perennial Flowers	To be Selected by Owner, See Landscape Plan	
Cleaning		
	House cleaned prior to closing, including washing of windows	
Warranty		
	Clearview Properties, LLC Warranty as per contract	
	Continuing a policy of constant research and improvement, Clearview Properties, LLC reserves	
	the right to make substitutions and specification changes.	



Appendix A: Window Schedule

Harvey Slimline All Vinyl Windows, Double insulated, Low E, GBG Grills 6 over 0 6 9/16 primed interior jambs, 2 1/2 colonial case interior

J Channel Only (Brickmould)

EZ-Tilt cleaning

Screens included

Energy Star Qualified

Maximum U Factor 0.30

Waxiiiiuiii o i actor t	Letter	Size	Quantity	Description	Location	Image	Notes
	А	34x65	5	Double Hung	Living Room, Dining Room		
	В	34x53	8	Double Hung	Owners Bedroom, Bedroom 2 & 3		
	С	34x41	1	Double Hung	Powder Room		
	D	34x49	1	Double Hung	Owner Bath		
	E	42x49	1	Double Hung	Kitchen		
	F	30x30	1	Awning	Stair Landing		
	G	34x34	2	Awning	Living Room		
	EG	55x48	1	Egress	Lower Level		



Appendix B: Exterior and Interior Door Schedule EXTERIOR DOORS

Therma-Tru Smooth Star Fiberglass Exterior Doors with full weather stripping and adjustable sills

6 9/16 primed jambs

5/4 x 4 flat exterior case, Double bore set-up

EZ Set Satin Nickel knob and deadbolt hardware, All doors keyed alike

	Quantity	Description	Opens	Size	Туре	Hardware	Image	Notes
Foyer Entry							'	
	1	S601 with S210SL Sidelite	RH	3'-0" 6'-8"	2 Panel	Double Bore		
Garage - Mudroom	n Entry						<u>'</u>	
	1	S220 2 Panel 6'-6" height	RH	3'-0" 6'-6"	2 Panel	Double Bore		
Dining Room Entry								
	1	S118	RH	3'-0" 6'-8"	Full Glass	Double Bore		
Exterior Door Hardv	vare						·	
Knobs	3	EZ - Set Keyed Entry w/deadbolt				Satin Nickel		All Keyed Alike
			IN ⁻	TERIOR DOORS			·	
Colonial Casing both EZ-Set Satin Nickel H Ball catches and (2) I Interior Doors		air included Masonite Smooth	See Plans - will display more clearly with plans	TBD	2 Panel Hollow Core	Double Bore		
	2	Masonite Smooth	See Plans - will display more clearly with plans	TBD	Double Doors	Double Bore		Pantry, Bedroom #3
Door to Future Bonus Room	1	Masonite Smooth	RH	TBD	Solid Core	Double Bore		with Threshold Weather Stripping
Interior Door Hardw	rare							
Knobs	14	EZ - Set				Satin Nickel		
Knobs	4	EZ - Set				Satin Nickel		Dummy for Ball Latch Double Door
Base Bumps	18					Satin Nickel		
Hinge Bumps	18					Satin Nickel	7	



						10,00 pt	J IVI E 3
		Appen	idix C: Light	Fixture Scheo	dule		
	Quantity	Description	SKU	Item	Color	Image	Notes
Garage Exterior							
	1	One Light Outdoor Wall Lantern	534299	Maxim 1024PE	Pewter		
Deck Exterior					1		
	1	One Light Outdoor Wall Lantern	967425	Maxim 1025PE	Pewter		
Front Porch							
	2	Click Lights - LED Flush Mount	040842	Green Creative	White		
Foyer							
	1	Three Light Semi Flush Mount	738584	Kichler 43669NI	Brushed Nickel		
Mudroom Hall							
	3	Click Lights - LED Flush Mount	040842	Green Creative	White		
Kitchen Island					1		
	2	One Light Mini Pendant	738588	Kichler 43668NI	Brushed Nickel		
Kitchen							
	5	Click Lights - LED Flush Mount	040842	Green Creative	White		
Kitchen Sink							
	1	Click Lights - LED Flush Mount	040842	Green Creative	White		



District Pages							
Dining Room				I		I .	I
	1	Five Light Chandelier	738590	Kichler 43665NI	Brushed Nickel	TINIT	
Living Room							
	1	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel		
Powder							
	1	Two Light Bath	738932	Kichler 45569NI	Brushed Nickel		Pointed Down
Stairwells							
	2	One Light Wall Sconce	738960	Kichler 45568NI	Brushed Nickel		1 - Main to Second Floor and 1 - in Main to Lower Level
Upstairs Hall							
	3	Click Lights - LED Flush Mount	040842	Green Creative	White		
Owners Bedroom							
	1	Three Light Flush Mount	725440	Maxim 2681FTSN	Satin Nickel		
Owners Vanity							
	2	Two Light Bath	738932	Kichler 45569NI	Brushed Nickel		Pointed Down
Owners Closet							
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel	-	



D. 1						1,0,0	J IVI L J			
edroom #2										
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel	*				
Bedroom #2 Closet										
	1	LED Ceiling Wrap	177424	Nuvo Lighting 65-1081	White					
Bedroom #3										
	1	Two Light Flush Mount	725441	Maxim 2680FTSN	Satin Nickel	*				
Bath #2										
	1	Three Light Bath	738938	Kichler 45570NI	Brushed Nickel		Pointed Down			
Other										
Garage, Future Bonus Room, Lower Level	12	PC Lights					Supplied by Electrician			



						п	OMES		
Appendix D: Plumbing Schedule									
	Qty.	Description	Manutacturer	Product No.	Finish	Image	Notes		
Kitchen									
Sink	1	32" Undermount 16 Gauge Stainless Steel Double Bowl Kitchen Sink	Krauss	KBU32	Stainless Steel		32" L x 18" W, 8.5"D (2) Strainers and Grates		
Faucet	1	Arbor Single-Handle Pull- Down Sprayer	Moen	7594C	Chrome				
Owner's Bath									
Faucet	2	Eva Two-Handle Sink Faucet	Moen	6410	Chrome				
Shower	1	Medley Shower Stall - 60" x 34"	Sterling	72430100-0	White		Straight Curtain Rod Installed.		
Shower Fixture	1	Eva Collection Eco- Performance Trim Kit	Moen	T2138EP	Chrome		Moen 2520 Shower Valve		
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White		16 1/2" Rim Height		



Bath #2						 J IVI E 3
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	
Tub/Shower	1	60-1/4" x 32" Curce Bath/Shower with LH Drain	Sterling	71220110-0	White	Straight Curtain Roc Installed.
Tub/Shower Trim	1	Eva Conversion Eco- Performance Tub/Shower Trim	Moen	T2139EP	Chrome	Moen 2520 Shower Valve
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White	16 1/2" Rim Height
Powder Bath						
Faucet	1	Eva Two-Handle Sink Faucet	Moen	6410	Chrome	
Pedestal Sink	1	Edgemere Pedestal Sink	American Standard	0445.400	White	
Toilet	1	Edgemere Right Height Elongated Toilet	American Standard	204AA.104	White	16 1/2" Rim Height



Appendix E: Finish Hardware Schedule										
	Qty.	Description	Manufacturer	Product No.	Finish	Image	Notes			
Owner's Bath					,					
Knob	7	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel					
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome					
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome					
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome					
owder Bath										
Towel Ring	1	Eva Bathroom Hand Towel Ring	Moen	YB2886CH	Chrome	2				
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome					
ath #2					<u>'</u>					
Knob	7	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel					
Robe Hook	1	Eva Single Robe Hook	Moen	YB2803CH	Chrome					
Tissue Holder	1	Eva Collection Pivoting Toilet Paper Holder	Moen	YB2808CH	Chrome					
Towel Bar	1	Eva 24 in. Towel Bar	Moen	YB2824CH	Chrome					
itchen Surround										
Knob	18	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel					
itchen Island										
Knob	4	Allison Value 1-1/4" Diameter Knob	Amerock	53005-G10	Satin Nickel					



Appendix F: Flooring Schedule

	WOOD								
Location	Make	Style	Finish	Size		Image			
Foyer, Hallway, Kitchen, Dining Room	Lauzon	Expert	TBD	TBD			Height 3/4"		
1	AA mina /Ch da	Finish /Oalan	TILE	0-111	Tile Count		Notes		
Location	Make/Style	Finish/Color	Tile Size	Orientation	Tile Grout	Image	Notes		
Owner's Bath	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Transitions to Dreamweaver Carpet.		
Mudroom	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Standard Underlayment. Transitions to 3/4" Wood.		
Powder	Anatolia Davenport	TBD	12 x 24	TBD	TBD		Standard Underlayment. Transitions to Mudroom Tile.		
			VINY	L					
Location	Make	Style	Color			Image	Notes		
Bath #2	Tarkett	Fresh Start	TBD	TBD	TBD		Transitions to Dreamweaver Carpet.		



HOMES								
Location	Make	Chilo	CARF Color	PET Details	I	lma m m m		
Locuilon	маке	Style	Color	Details		Image		
Living Room	Dreamweaver	Pinpoint	TBD				Transitions to 3/4" Wood.	
Owner's Bedroom, Owners WIC	Dreamweaver	Pinpoint	TBD				Transitions to Owners Bath Tile.	
Bedroom 2, Bedroom 3	Dreamweaver	Pinpoint	TBD				Transitions to Dreamweaver Carpet.	
Upstairs Hall, Staircase to Second Floor	Dreamweaver	Pinpoint	TBD				Transitions to 3/4" Wood.	



		۸n	pendix G: Appl	liance Scho	dula		O IVI E S
Appliance	Quantity	Manufacturer	Model	Color	Description	lmage	Notes
Kitchen							
Refrigerator	1	GE	GNE27JYMFS	Stainless	GE Energy Star 27.0 Cu. Ft. French Door		Fingerprint Resistant Door
Gas Range	1	GE	JGB735SPSS	Stainless	GE 30" Free Standing Gas Convection Range		
Dishwasher	1	GE	GDT550PYRFS	Stainless	GE Dishwasher with Top Controls	9	
Microwave	1	GE	JVM3160RFSS	Stainless	GE 1.6 Cu. Ft. Over- the-Range- Microwave Oven		
Laundry Room							
Washer							Available as option
Electric Dryer							Available as option