


Acoustic Waveform Processing



**BAKER
HUGHES**

Baker Atlas

MULTIPOLE ARRAY ACOUSTILOGSM AZIMUTHAL ANISOTROPY ANALYSIS

COMPANY SIERRA GEOTHERMAL POWER, INC.

WELL ALUM 25-29

FIELD ALUM

COUNTY ESMERALDA STATE NEVADA

LOCATION: 2235.18' FSL & 938.11' FWL

SEC 29 TWP 1N RGE 38.5E

ELEVATIONS:

KB 4919.57 FT DF N/A GL 4903.57 FT

DATE 23-NOV2009 ECC _____

IN MAKING INTERPRETATIONS OF LOGS OUR EMPLOYEES WILL GIVE CUSTOMER THE BENEFIT OF THEIR BEST JUDGEMENT. BUT SINCE ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS, WE CANNOT, AND WE DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATION. WE SHALL NOT BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COST, DAMAGES, OR EXPENSES WHATSOEVER INCURRED OR SUSTAINED BY THE CUSTOMER RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR EMPLOYEES.

REMARKS

DATA MAY BE UNRELIABLE IN AREAS OF TENSION PULLS & WASHOUT
MAGNETIC DECLINATION: 14.4 DEG
FAST & SLOW WAVE DIRECTIONS MAY BE UNRELIABLE WHERE ANI<3%

ANALYSIS: J. ADREON

AZIMUTHAL ANISOTROPY MAP


CURVE MEASURE POINT OFFSET

CURVE	OFFSET (ft)	CURVE	OFFSET (ft)	CURVE	OFFSET (ft)	CURVE	OFFSET (ft)
ANI	20.75	CAL	81.50	FAP1	20.75	GR	99.00
ANIA	14.75	DEVXEQ1	14.00	FNEG	20.75		
AZSH	14.00	FACR	20.75	FPOS	20.75		

Project : /geos/lac/adrejosl/sierra_xmac
 User : adrejosl
 Presentation : sunserv24:/geos/lac/adrejosl/sierra_xmac/map.pdf [10"/100' Scale]
 Plot Interval : 590 - 2280 Feet









Data File 1 : F1 : sunserv24:/geos/lac/adrejosl/sierra_xmac/xmac.xtf
 Created On : Nov 15 12:51:25 2009
 Company : SIERRA GEOTHERMAL POWER, INC.
 Well : ALUM 25-29
 Field : ALUM
 File Interval : 472.5 - 2316 Feet
 Oct : k7711


Data File 2 : F2 : sunserv24:/geos/lac/adrejosl/sierra_xmac/ani.xtf
 Created On : Nov 15 12:51:25 2009
 Company : SIERRA GEOTHERMAL POWER, INC.
 Well : ALUM 25-29
 Field : ALUM
 File Interval : 472.5 - 2316 Feet
 Oct : k7711






FEET

600












900




950









1100

1150













1550




1600










1750






1800















2200




2250



FAST AZIMUTH [facr]

700


Angle Uncertainty





AZIMUTHAL ANISOTROPY ANALYSIS


Project : /geos/lac/adrejos/sierra_xmac
 User : adrejos
 Presentation : sunserv24:/geos/lac/adrejos/sierra_xmac/anisotropy-qc.pdf [5"/100' Scale]
 Plot Interval : 590 - 2308 Feet


 Data File 1 : F1 : sunserv24:/geos/lac/adrejos/sierra_xmac/ani.xtf
 Created On : Nov 15 12:51:25 2009
 Company : SIERRA GEOTHERMAL POWER, INC.
 Well : ALUM 25-29
 Field : ALUM
 File Interval : 472.5 - 2316 Feet
 Oct : k7711























Gamma Ray [gr] (gAPI) 0 150	S1S0	TOOL STICKING	500	WINDOW START [wdst]	6500	ANISOTROPY	SLOW AZIMUTH
Caliper [cal] (inches) 14 24	S1S2	FAST DT [dtsf] (us/ft)	440 40	(us)		ANISOTROPY [ani] (%)	(deg)
Tool Azimuth [azsh] (deg)	S2IS	SLOW DT [dtss] (us/ft)	440 40	500	WINDOW_END [wend]	20	0 180
dev (deg)		DTS (us/ft)	440 40	500	Fast Wavetrace		Corr. FAST AZIMUTH
		TENSION [ten] (lbs)	5000 40	500	Slow Wavetrace		0 180
				6500			(deg)

PARAMETER SECTION

